



M-1500 PU EPOXY INJECTION MACHINE



UNIFIX M-1500 is one-component grouting injector which is used to inject epoxy or polyurethane filling materials to waterleaking cracks.

UNIFIX M-1500 can generate a working pressure of 10000psi only within 6 seconds.

Portable body, weighing only 10 kg, easy to carry & maintain, maximum output pressure up to 15,000psi. The fault can be self-maintenance during site operation. The medicament can also be injected into small cracks and pores. (larger than 0.01mm).

UNIFIX M-1500 is a professional Injection Pump in the field of filling resin into the concrete structure.

Since it is manufacture to be small-sized and medium weighted, it can be an essential device at a concrete repair site.

SCOPE OF APPLICATION

Leak-stoppage, Waterproof & Reinforcement for Concrete Structure, such as Basement, Floor, the second Joints, Subway, Tunnel, Continuous Wall, Cracks, Water Seepage, etc.

MATERIAL APPLICATION

PU foam stop leakage agent, Epoxy resin, non-granular mobile-liquid.

SPECIFICATIONS

Weight	10 kg
Maximum output pressure	15,000 psi
Pressure of starting again	7,000 psi
Safe range of high-pressure hose	10,000 psi
Safe range of switch valve	15,000 psi

ACCESSORIES

Power drill	1200w
High pressure hose	1 roll 5m
Shut-off valve	1 set
Repairing kit	1 set
Seal set	1 set
T type wrench	1 set



UNIFIX PACKER & PACKER CONNECTOR

PROFILES	SIZE	PACKING
UNIFIX A10	13mm x 90mm	50 pcs / bag
UNIFIX A15	13mm x 130mm	50 pcs / bag
UNIFIX A20	13mm x 180mm	50 pcs / bag
UNIFIX A25	13mm x 240mm	50 pcs / bag
UNIFIX A30	13mm x 280mm	50 pcs / bag
UNIFIX B8	10mm x 80mm	100 pcs / bag
UNIFIX B10	10mm x 100mm	100 pcs / bag
GREASE HEAD	A10 / B10 Connector	10 pcs / box



PRESSURE INJECTION HOSE

WORKING PRESSURE	0 - 10,000 psi
SIZE	5 meter long



UNITY RELIANCE (M) SDN BHD 6-2, Jalan Meranti SD13/5, Bandar Sri Damansara 52200 Petaling Jaya Selangor.

Website:https://www.unityreliance.comEmail:unityreliance88@gmail.comTel:03 - 6263 0139 / 010 - 785 1159